Application No.: 10/751,510 Art Unit: 1723

Attorney Docket No.14991.01 Confirmation No.3347

IN THE CLAIMS:

This listing of claims will replace all prior versions, and listings, of claims in the

application:

Listing of Claims:

Claims 1-11. (Canceled)

Claim 12. (Currently Amended) A combination filter insert and rain gutter comprising:

an elongated filter insert having a cross section in the form of a truncated right

triangle and made of open cell foam porous material, said filter insert having a generally

horizontal upper side with front and rear edges, a generally vertical rear side

perpendicular to said upper side and having an upper edge coincident with said rear edge

of said upper side and a lower edge, a planar generally flat, angled side extending

between the front edge of said upper side to a lower forward edge proximate to and

forward of the lower edge of said rear side and rearward of the upper side front edge, a

lower side parallel with said upper side and extending forward from said lower edge of

said rear side to said lower forward edge, said lower side of said filter insert being formed

by the truncation of said filter insert between said rear side and said planar angled side;

2

and

Attorney Docket No.14991.01 Confirmation No.3347

Application No.: 10/751,510

Art Unit: 1723

a rain gutter having a back wall, a bottom wall, and a front wall, said front wall

having an upper lip, an upper opening defined between said back wall and said front wall

upper lip,

said filter insert being inserted into said rain gutter such that said insert upper side

spans said gutter upper opening between said back wall and said upper lip of said front

wall, said rear side of said insert bearing against and coextensive with said gutter back

wall, and said insert lower side bearing against said gutter bottom wall, said insert planar

angled side extending between said lower side at said lower forward edge to said gutter

front wall upper lip, wherein said planar angled side of said insert faces said front wall

and said bottom wall of said gutter, and wherein a void having a substantially triangular-

shaped cross section is defined between said planar angled side of said insert, said front

wall and said bottom wall of said gutter, whereby liquid may enter said gutter upper

opening and travel through said filter insert into said void, for flow to a gutter liquid

outlet while leaves and other debris are trapped on the upper side of said filter insert.

Claim 13. (Previously Presented) The combined filter insert and gutter of claim 12,

wherein said open cell porous foam material has from about 10 to about 20 cells per

square inch.

3

Attorney Docket No.14991.01 Confirmation No.3347

Application No.: 10/751,510 Art Unit: 1723

Claim 14. (Previously Presented) The combined filter insert and gutter of claim 13,

wherein said open cell porous foam material is flexible polyether foam.

Claim 15. (Previously Presented) The combined filter insert and gutter of claim 12, wherein

said filter insert is about four feet in length.

Claim 16. (Previously Presented) The combined filter insert and gutter of claim 12,

wherein said gutter has an inner lip portion extending inward and downward from said

upper lip so as to bear against said upper side of said filter insert.

Claim 17. (Previously Presented) The combined filter insert and gutter of claim 12,

wherein said gutter is mounted on a building structure below the eave of a roof such that

rainwater draining from said roof enters said gutter through said filter insert upper side.

4

Application No.: 10/751,510 Art Unit: 1723

Confirmation No.3347

Attorney Docket No. 14991.01

Claim 18. (Previously Presented) The combined filter insert and gutter of claim 17,

further comprising a plurality of spaced gutter spikes extending through said gutter upper

lip, across said span formed between said upper lip and said back wall, and through said

back wall into said building structure for securing said gutter to said building structure,

said filter insert fitting below said gutter spikes.

Claim 19. (Previously Presented) The combined filter insert and gutter of claim 12,

wherein said filter insert is about four feet in length and a plurality of filter inserts are

inserted end to end into a length of said gutter so as to extend the full length of said

gutter.

Claim 20. (Previously Presented) The combined filter insert and gutter of claim 19

wherein said filter inserts are easily removed from the gutter for cleaning and are easily

reinstalled into the gutter.

5